


NHM Series Hydraulic Motor

Product Feature:

NHM series of low-speed and high-torque hydraulic motors with crankshaft and connecting rod are produced according to the technology and standard provided by Italy. On such a foundation, we also have constant technological improvement according to market demand, so as to improve the performance of the products.

The main features include:

1. Low noise due to an eccentric crankshaft and low excitation frequency of five-piston design;
2. Revolve steadily under very low speed due to high starting torque and good low-speed stability;
3. Good reliability and less leakage due to the patented flat compensation distributor, special sealing between piston and plunger bushing guarantees higher volumetrical efficiency;
4. High mechanical efficiency due to roller bearing between crankshaft and connecting rod;
5. Reversible rotation, and the output shaft can bear certain external force from both radial and axial directions;
6. High power-mass ratio, small volume and light weight.



Calculation:

1. Actual output torque : $M=0.159 (P_1-P_2) V \cdot \eta_m (N.m)$

where : P_1, P_2 ----- (MPa) inlet and outlet pressure (MPa)
 V ----- displacement (ml/r)
 η_m -----mechanical efficiency (%)

2. Output power : $N = \frac{M \cdot n}{9550} (kW)$ $N = \frac{q (P_1 - P_2)}{60000} \eta_m \eta_v (kW)$


where : n ----- speed (r/min)
 q ----- input flow (ml/min)
 η_v ----- volumetrical efficiency (%)

3. Speed : $n = \frac{q}{V} \eta_v (r/min)$

Note:

1. Filtration: the recommended filtration precision for normal industrial use is 25 μ m, and allowable precision low pressure, low speed or interval is 75 μ m.
2. Oil viscosity: the optimum performance could only be obtained under proper oil viscosity between 15–1000cst.
3. Before the first start-up, it must fill hydraulic oil in the hydraulic motor body, to avoid the damage.
4. Leakage: drain port should be connected separately to the tank. Normally the maximum pressure for the motor body is 0.1 Mpa, and it could also be improved to bear 3–5 Mpa, to meet special requirements.
5. The top line of the drain pipe should be higher than that of the motor body, in case emptying oil storage.
6. Installation: motor can be installed in any position with rigid support, When installed, shafts of the motor and its transmission should be concentric.
7. Cleanness: Strictly maintain the cleanness of the oil port, and keep any solid particles away.
8. Release both the radial and axial loads of the output shaft to enable longer life of the motor.
9. NHM motor could not work as a pump.

Order Code




"Left deviation" and "Right deviation" are only applicable for NHM2–NHM11 series of motors, and oil inlet and outlet are horizontal. (Same as illustrated)


Technical specification:

Type NHM	Displacement (ml/r)	Pressure (MPa)		Torque (N.m)		Speed Range (r/min)	Weight (kg)	
		(Rated Pressure)	(Max Pressure)	Rated Torque	(N.m/MPa) Theoric Specific Torque			
NHM1-63	77	25	32	284	11	15-1500	20	
NHM1-80	91	25	32	335	13	15-1250		
NHM1-100	96	25	32	355	14	15-1000		
NHM1-110	113	25	32	419	17	15-1000		
NHM1-125	126	20	25	371	19	15-1000		
NHM1-140	138	20	25	410	20	15-1000		
NHM1-160	159	16	20	376	24	15-1000		
NHM1-200	196	16	20	464	29	15-800		
NHM2-100	113	25	32	419	17	15-1250	27	
NHM2-125	138	25	32	512	20	15-1250		
NHM2-150	159	25	32	588	24	15-1000		
NHM2-175	180	20	25	532	27	15-1000		
NHM2-200	207	20	25	611	31	8-800		
NHM2-250	235	16	20	556	35	8-630		
NHM2-280	276	16	20	653	41	8-500		
NHM3-175	181	25	32	670	27	8-1000	35	
NHM3-200	201	25	32	743	30	8-800		
NHM3-220	222	25	32	819	33	8-800		
NHM3-250	254	20	25	752	38	8-630		
NHM3-300	289	20	25	856	43	6-500		
NHM3-350	340	20	25	1000	50	6-400		
NHM3-400	380	18	22.5	1008	56	6-350		
NHM6-400	397	25	32	1469	59	5-630	57.5	
NHM6-450	452	25	32	1672	67	5-630		
NHM6-500	491	20	25	1451	73	5-500		
NHM6-600	594	20	25	1756	88	4-500		
NHM6-700	683	16	20	1616	101	4-400		
NHM6-750	754	16	20	1785	112	4-320		
NHM8-600	617	25	32	2282	91	4-500		72
NHM8-700	710	25	32	2626	105	4-400		
NHM8-800	810	20	25	2396	120	4-400		
NHM8-900	889	20	25	2629	131	3-350		
NHM8-1000	1000	16	20	2366	148	3-300		
NHM11-700	707	25	32	2612	104	4-400	94	
NHM11-800	784	25	32	2899	116	4-400		
NHM11-900	894	25	32	3306	132	4-400		
NHM11-1000	981	20	25	2902	145	3-320		
NHM11-1100	1104	20	25	3265	163	3-320		
NHM11-1200	1234	16	20	2919	182	3-320		
NHM11-1300	1301	16	20	3079	192	3-250		
NHM16-1400	1413	25	32	5224	209	2-400	170	
NHM16-1600	1648	20	25	4874	244	2-400		
NHM16-1800	1815	20	25	5367	268	2-350		
NHM16-2000	2035	18	22.5	5416	301	2-350		
NHM16-2400	2267	16	20	5364	335	2-250		
NHM31-2500	2553	25	32	9438	378	2-200		298
NHM31-2800	2683	20	25	7935	397	1-200		
NHM31-3000	3063	20	25	9057	453	1-200		
NHM31-3150	3218	20	25	9518	476	1-160		
NHM31-3500	3561	20	25	10530	527	1-160		
NHM31-4000	4153	18	22.5	11053	614	1-160		
NHM31-4500	4522	16	20	10698	669	1-160		
NHM31-5000	4828	16	20	11423	714	1-160		
NHM70-5000	4968	20	25	14626	731	1-160	550	
NHM70-5400	5452	20	25	16125	806	1-160		
NHM70-6000	5984	20	25	17697	885	0.5-125		
NHM70-6300	6540	18	22.5	17408	967	0.5-125		
NHM70-7000	7122	16	20	16849	1053	0.5-125		


NHM1-63~200 Mounting Data




Standard outside spline
NHM1-**




Standard parallel key
NHM1-**B




NHM1-**B₃




NHM1-**B₁₁ B₁₁-1




NHM1-**B₂₈




NHM1-**B₃₁




NHM2-100~280 Mounting Data




Standard outside spline
NHM2-**




NHM2-**SL₁




Standard parallel key
NHM2-**B




NHM2-**H₁




Standard inside spline
NHM2-**1




NHM2-**B₁, B₂




NHM2-**B₃




NHM2-**B₅




NHM2-**B₁₄




NHM2-**B₂₄



NHM2-**B₄₃




NHM2-**I₀₁I₀₂




INTERMOT
HYDRAULIC MOTOR


NHM3-175~400 Mounting Data




Standard outside spline
NHM3-***




Spline key shaft
NHM3-***A




Standard parallel key
NHM3-***B




NHM3-***SL₁



Standard inside spline
NHM3-***I




NHM3-***SL₂, SL₃




Type	D
SL ₂	195
SL ₃	250


NHM3-***B₁




NHM3-***B₂




NHM3-***B₅




NHM3-***B₃₂



NHM3-***B₄₄




NHM3-***I_{1A1}




INTERMOT
HYDRAULIC MOTOR




NHM6-400~750 Mounting Data




Standard outside spline
NHM6-**




Standard parallel key
NHM6-**B




Standard inside spline
NHM6-**1




NHM6-**SL₂




NHM6-**SL₃




NHM6-**N




NHM6-**N₁




NHM6-**B₂




NHM6-**B₄




NHM6-**B₅




NHM6-**B₁₃




NHM6-**B₃₃




NHM6-**B₄₅




NHM6-**I₁₁



NHM8-600~1000 Mounting Data




Standard outside spline
NHM8-**





NHM8-**6MB

Standard parallel key
NHM8-**B




NHM8-**a2


parallel shaft
NHM8-**6M



NHM11-700~1300 Mounting Data




Standard outside spline
NHM11-**




NHM11-**SL₃

Standard parallel key
NHM11-**B






NHM11-**SL₄

Standard inside spline
NHM11-**I




NHM11-**SL₅




NHM11-700~1300 Mounting Data


NHM11-**SM₄




NHM11-**N




NHM11-**N₁




NHM11-**K




NHM11-**B₄




NHM11-**B₆




NHM11-**B₃₅





NHM11-**B₄₆




NHM11-**I₂₁




NHM16-1400~2400 Mounting Data




Standard outside spline NHM16-**




Standard parallel key NHM16-**B




Standard inside spline NHM16-**I




NHM16-**SL₅










NHM16-**SM₄



NHM16-**N









NHM16-1400~2400 Mounting Data



INTERMOT
HYDRAULIC MOTOR




NHM31-2500~5000 Mounting Data




NHM31-2500~5000 Mounting Data


NHM31-**B₁₀




NHM31-**B₂₁




NHM31-**B₂₂




NHM31-**H6



NHM31-**I₅₃₂





NHM31-**I₅₂




INTERMOT
HYDRAULIC MOTOR




NHM70-5000~7000 Mounting Data




Standard parallel key
NHM70-**B




NHM70-**a₁




NHM70-**a₃



NHM70-**B₁



NHM70-**B₂



Standard parallel key
NHM70-**BC

